



## NC3FM-C-B

World's first 3 pole unisex XLR cable connector,  
black

### Features & Benefits

- ✓ World's first unisex XLR
- ✓ 3 pole male and female cable connector in one housing
- ✓ Easy selectable gender - converted by sliding housing back and forth
- ✓ Substitute adapters, ideal as an emergency kit
- ✓ With all benefits of the XLR XX series

### Technical Information

Product	
Title	NC3FM-C-B
Connection Type	XLR
Gender	female

**Electrical**

Capacitance between contacts	$\leq 4 \text{ pF}$
Contact resistance	$\leq 3 \text{ m}\Omega$
Dielectric strength	1.5 kVdc
Insulation resistance	$> 2 \text{ G}\Omega$ (initial)
Rated current per contact	16 A
Rated voltage	$< 50 \text{ V}$

**Mechanical**

Cable O.D.	3.5 - 8.0 mm
Insertion force	$\leq 20 \text{ N}$
Withdrawal force	$\leq 20 \text{ N}$
Lifetime	$> 1000$ mating cycles
Wiresize	max. $2.5 \text{ mm}^2$
Wiresize	max. 14 AWG
Wiring	Solder contacts
Locking device	Latch lock

Material	
Boot	Polyurethan
Contact plating	0.2 µm Au
Contacts	Brass (CuZn39Pb3) (male)
Insert	Polyamide (PA 6.6 30 % GR)
Locking element	Zinc diecast (ZnAl4Cu1) / Ck 67 (spring)
Shell	Black chromium
Shell plating	Nickel
Strain relief	Polyacetal (POM)

Environmental	
Flammability	UL 94 HB
Standard compliance	IEC 61076-2-103
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C