

PUBLIC ADDRESS / SPEAKERS / SURFACE

SONORA-3-BK

LOW IMPEDANCE SURFACE SPEAKER



- ✓ Defined sound and great fidelity
- ✓ Excellent finish and elegant design
- ✓ Outdoor installation
- ✓ Quick and easy installation



+ Info:

<https://fonestar.com/SONORA-3-BK>

ESPECIALLY RECOMMENDED IN:



Hospitality



Education



Hotels



All sectors

DESCRIPTION

3" surface speaker. 12 W RMS@8Ohm. IP66 protection and salt fog. Adjustable fixing mount.

TECHNICAL CHARACTERISTICS


FEATURES	Low impedance sound reinforcement speaker. Ready for outdoor use, with IP-66 protection.
POWER	20 W max., 12 W RMS
LOUDSPEAKERS	1 woofer polypropylene 3"
RESPONSE	130-20,000 Hz (-10 dB)
PROTECTIONS	IP-66 in compliance with EN 60529 IEC 60068-2-11 Environmental Test (Salt mist)
IMPEDANCE	8 Ohm
SENSITIVITY	84 dB @ 1 W/1 m
MAXIMUM SOUND PRESSURE	94 dB @ max. W/1 m
COVERAGE ANGLE	H/V: 270°/270°@500 Hz, 180°/180°@1 kHz, 120°/120°@2 kHz, 100°/100°@4 kHz (-6 dB)
MATERIAL	ABS (UV resistance) Aluminium mesh grille, with powder-coated finish Weather-resistant mount A2 stainless steel screws
CONNECTORS	Euroblock in and out for cable 0.25 - 2.5 mm² cross section
TEMPERATURE RANGE	-10°C ~ 60°C
COLOUR	Black (RAL 9005)
DIMENSIONS	Speaker: 97 x 110 x 107 mm depth Support wall plate: 67 x 71 mm Speaker with support: 150 mm depth
WEIGHT	0.5 kg
ACCESSORIES	Adjustable fixing support H: ±30°, V: +15°/-45°




+ Info:

<https://fonestar.com/SONORA-3-BK>


SENSITIVITY (SPL)




IMPEDANCE



POLAR DATA






FONESTAR

Model:
SONORA-3-WH+SONORA-3-BK

Description:
LOW IMPEDANCE SURFACE SPEAKER

Unit:
mm

Scale:
1:2




FONESTAR

Model:
SONORA-3-WH+SONORA-3-BK

Description:
LOW IMPEDANCE SURFACE SPEAKER

Unit:
mm

Scale:
1:2



FONESTAR

Model:
SONORA-3-WH+SONORA-3-BK

Description:
LOW IMPEDANCE SURFACE SPEAKER

Unit:
mm

Scale:
1:2