

PUBLIC ADDRESS / SPEAKERS / SURFACE

SONORA-4TB-EN

SURFACE LOUDSPEAKER WITH 100 V LINE TRANSFORMER AND LOW IMPEDANCE IN COMPLIANCE WITH EN 54



- ✓ Excellent sound quality
- ✓ Excellent finish and elegant design
- ✓ EN 54-24 certificate
- ✓ Prepared for outdoor use, protection against water and anti-corrosion materials.



<https://fonestar.com/SONORA-4TB-EN>

ESPECIALLY RECOMMENDED IN:



Hospitality



Education



Hotels



All sectors

DESCRIPTION

4" surface speaker. 30/15/7.5/3.75 W RMS@100 V. 30 W RMS@8Ohm. IP66 protection. Adjustable fixing mount. Steel safety cable. EN 54 certificate.

TECHNICAL CHARACTERISTICS

FEATURES	Loudspeaker for voice alarm systems EN 54 Low-impedance loudspeaker with 100 V line transformer. Prepared for outdoor use, waterproof and rustproof materials.
INTENDED USE	Loudspeaker for voice alarm systems
STANDARDS	Certified EN 54-24 Fire detection and fire alarm systems - Part 24: components of voice alarm systems - Speakers EN 54-24: 2008
POWER	60 W max., 30 W RMS
LOUDSPEAKERS	1 x 4" woofer 1 x 1" tweeter
RESPONSE	120-20,000 Hz
IMPEDANCE	30 W RMS@100 V (333 Ohm) 15 W RMS@100 V/70 V (667 Ohm/326 Ohm) 7.5 W RMS@100 V / 70 V(1.333 Ohm/ 653 Ohm) 3.75 W RMS@100 V / 70 V(2.667 Ohm/ 1.306 Ohm) 1.9 W RMS@70 V (2.579 Ohm) Low Z: 8 Ohm
SENSITIVITY	83 dB @ 1 W/1 m 72 dB @ 1 W/4 m
MAXIMUM SOUND PRESSURE	96 dB @ max. W/1 m 85 dB @ max. W/4 m
COVERAGE ANGLE	145° H x 130° V @1kHz (-6 dB)
PROTECTION	Type B IP-66 in compliance with EN 60529 IEC 60068-2-11 Environmental tests (Saline mist)
MATERIAL	ABS 5VB (UV resistance) Aluminium mesh grille, with powder-coated finish Weather-resistant mount A2 stainless steel screws



+ Info:

<https://fonestar.com/SONORA-4TB-EN>

SWITCH	W selector in high Z and low Z
CONNECTORS	Euroblock for cable 0.25 – 2.5 mm ² cross section
TEMPERATURE RANGE	–10°C ~ 60°C
COLOUR	White (RAL 9003)
DIMENSIONS	125 x 202 x 120 mm depth
WEIGHT	1.6 kg
ACCESSORIES	Adjustable mounting bracket ± 60° in all directions. Steel safety cable



+ Info:

<https://fonestar.com/SONORA-4TB-EN>