MICROPHONE / CONFERENCE SYSTEMS / STANDARD

MIC-SCF-D

DELEGATE MICROPHONE FOR CONFERENCE SYSTEM MOD. SCF-250.





- Crystal clear voice pick-up
- Metal microphone base

+ Info:
https://fonestar.com/MIC-SCF-D

ESPECIALLY RECOMMENDED IN:



Education



Offices

DESCRIPTION

Delegate microphone for conference system mod. SCF-250.

TECHNICAL CHARACTERISTICS

CAPSULE	Unidirectional electret condenser
RESPONSE	50-20,000 Hz
SENSITIVITY	-42 dB ±3 dB (V/Pa) at 1 kHz
IMPEDANCE	600 Ohm
SPL MAX	128 dB
EQUIVALENT NOISE	33 dB
DYNAMIC RANGE	95 dB
DISTORTION (THD)	<1 %
SNR	61 dB
INDICATORS	LED power indicator LED operation ring
TEMPERATURE	Operating temperature: -20 ºC - 50 ºC Storage temperature: -25 ºC - 70 ºC Relative humidity: 0 - 90 %
CONNECTORS	Input: XLR female 3 PIN Output: DIN male 8 PIN
POWER SUPPLY	18 V DC, supplied by the control unit
CABLE	1'2 m DIN male 8 PIN
DIMENSIONS	Gooseneck microphone: 45 cm height Base: 93 x 46 x 122 mm depth
WEIGHT	0'68 kg
ACCESSORIES	Wind-shield foam 1 Y interconnect cable, 2 m + 0'2 m DIN 8 male to 2 DIN 8 female
COMPATIBILITY	SCF-250: Conference system



+ Info:
https://fonestar.com/MIC-SCF-D