MICROPHONE / CONFERENCE SYSTEMS / STANDARD

# MIC-SCF-P

CHAIRMAN MICROPHONE FOR CONFERENCE SYSTEM MOD. SCF-250.






- Crystal clear voice pick-up
- Metal microphone base

+ Info:
https://fonestar.com/MIC-SCF-P

ESPECIALLY RECOMMENDED IN:


Sports facilities


Education


Hotels


Offices

## DESCRIPTION

Chairman microphone for conference system mod. SCF-250.

## TECHNICAL CHARACTERISTICS

| | |
|---|---|
| CAPSULE | Unidirectional electret condenser |
| RESPONSE | 50-20,000 Hz |
| SENSITIVITY | -42 dB ±3 dB (V/Pa) at 1 kHz |
| IMPEDANCE | 600 Ohm |
| SPL MAX | 128 dB |
| EQUIVALENT NOISE | 33 dB |
| DYNAMIC RANGE | 95 dB |
| DISTORTION (THD) | <1 % |
| SNR | 61 dB |
| INDICATORS | LED power indicator<br>LED operation ring |
| OPERATION | ON-OFF push-button (PTL)<br>Priority over the rest of the microphones |
| TEMPERATURE | Operating temperature: -20 ºC - 50 ºC<br>Storage temperature: -25 ºC - 70 ºC<br>Relative humidity: 0 - 90 % |
| CONNECTORS | Input: XLR female 3 PIN<br>Output: DIN male 8 PIN |
| POWER SUPPLY | 18 V DC, supplied by the control unit |
| CABLE | 1.2 m DIN male 8 PIN |
| DIMENSIONS | Gooseneck microphone: 45 cm height<br>Base: 93 x 46 x 122 mm depth |
| WEIGHT | 0'68 kg |
| ACCESSORIES | Wind-shield foam<br>1 Y interconnect cable, 2 m + 0'2 m DIN 8 male to 2 DIN 8 female |


+ Info:
https://fonestar.com/MIC-SCF-P

| COMPATIBILITY | SCF-250: Conference system |
|---|---|

+ Info:
https://fonestar.com/MIC-SCF-P