



## NC3FAAH2

3 pole female XLR receptacle, grounding: separate ground contact to mating connector shell and front panel, horizontal PCB mount

Most cost-effective round plastic body XLR PCB mount panel connector. Front panel cutout and PCB layout 100% compatible to A series. "Tulip" type contact design with high contact pressure for highest durability. Push latch assembled. Flammability rating UL94HB. UL recognized component.

## Features & Benefits

- ✓ Most cost-effective series
- ✓ "Tulip" type contact design with high contact pressure for highest durability
- ✓ Selective gold plated contact and PCB termination area for best conductivity and solderability

## Technical Information

Product	
Title	NC3FAAH2
Connection Type	XLR
Gender	female

<b>Electrical</b>	
Capacitance between contacts	$\leq 4$ pF
Contact resistance	$\leq 6$ m $\Omega$
Dielectric strength	1,5 kVdc
Insulation resistance	$> 10$ G $\Omega$ (initial)
Rated current per contact	6 A
Rated voltage	$< 50$ V
Grounding Options	Separate ground contact connected to mating connector shell and front panel, no connection to Pin 1

<b>Mechanical</b>	
Insertion force	$\leq 20$ N
Withdrawal force	$\leq 20$ N
Lifetime	$> 1000$ mating cycles
Wiresize	
Wiring	Horizontal PCB mount
Locking device	Latch lock
Mounting direction	Rear mounting
Chassis shape	A
Mounting	A-Screw

Material	
Contacts	Bronze (CuSn6)
Locking element	Steel Ck67
Locking element plating	Nickel
Shell	Polyamide (PA 6.6 30 % GR)

Environmental	
Approvals	UL
Flammability	UL 94 HB
Standard compliance	IEC 61076-2-103
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C