



## NE8MX6-B-T

etherCON CAT6<sub>A</sub> cable connector self-termination,  
for insulation diameter  $\leq$  1.1 mm, black chromium

The set NE8MX6 consists of a cable plug carrier offering a robust metal shell, proven Neutrik chuck-type strain relief and a CAT6<sub>A</sub> compliant RJ45 plug. The set is suitable for a cable diameter range of 7 mm to 9.5 mm and wire gauge of AWG26/1 - AWG24/1 (solid) or AWG27/7 - AWG24/7 (stranded).

Attention! Does not intermate with the CAT6 chassis connectors NE8FDY-C6 and NE8FDY-C6-B.

If the insulation diameter is  $>$  1.1 mm please refer to [NE8MX6-B](#).

## Features & Benefits

- ✓ Ruggedized connector with CAT6<sub>A</sub> component compliance according to ISO/IEC 11801 and TIA/EIA 568-C.2
- ✓ PoE++ compliant according to 802.3bt Type4
- ✓ IP65 protected when mated with NE8FDX-P6-W or NE8FDX-Y6-W
- ✓ Rugged latch lock system million fold proven
- ✓ Intermateable with the existing etherCON CAT5 range
- ✓ Unique Neutrik chuck-type strain relief

## Technical Information

Product	
Title	NE8MX6-B-T
Connection Type	etherCON
Gender	male
Electrical	
Dielectric strength	1 kVdc
Insulation resistance	> 0.5 GΩ
Rated current per contact	1.5 A
Transmission performance	CAT6A, acc. TIA/EIA rating CAT6A, acc. IEC/ISO/EN rating
Power over Ethernet	PoE++ acc. IEEE 802.3bt
Mechanical	
Cable O.D.	7.0 mm - 9.5 mm
Lifetime	> 1000 mating cycles
Wiresize	AWG 26/1 – AWG 24/1 (solid) AWG 27/7 – AWG 24/7 (stranded)
Locking device	Latch lock
Insulation diameter	0.85-1.1mm

<b>Material</b>	
<b>Bushing</b>	PA / PU
<b>Contact plating</b>	Au
<b>Shell</b>	Zinc diecast (ZnAl4Cu1)
<b>Shell coating</b>	Black KTL
<b>Strain relief</b>	POM

  

<b>Environmental</b>	
<b>Protection class</b>	IP 65 (in combination with NE8FDX-*6-W)
<b>Temperature range</b>	-40 °C to +70 °C