

PUBLIC ADDRESS / SPEAKERS / SOUND PROJECTORS

PF-1020T-EN

SOUND PROJECTOR WITH 100 V LINE TRANSFORMER AND LOW IMPEDANCE. EN 54 CERTIFIED



IP66

- ✓ Loudspeaker for voice alarm and fire evacuation systems, 20 W
- ✓ EN 54-24 certificate
- ✓ Exceptional sound for voice and musical ambience.
- ✓ Great sound coverage
- ✓ Suitable for indoor and outdoor PA installations IP66 protection



+ Info:

<https://fonestar.com/PF-1020T-EN>

ESPECIALLY RECOMMENDED IN:



Factories



Education



Transport Stations



All sectors

DESCRIPTION

Sound projector. 20/10/5/5 W RMS@100 V and 20 W RMS@8 Ohm. EN 54 certificate. IP-66 protection.

TECHNICAL CHARACTERISTICS

FEATURES	Loudspeaker for voice alarm system EN 54 Sound projector. 100 V line transformer and low impedance. Prepared for outdoor use, have protection against water and anti-corrosion materials.
STANDARD	EN 54-24 certified
POWER	20 W RMS
SPEAKERS	5" full-range
RESPONSE	120-21,000 Hz (-10 dB)
IMPEDANCE	20 W RMS@100 V / 10 W RMS@70 V (500 Ohm) 10 W RMS@100 V / 5 W RMS @70 V (1000 Ohm) 5 W RMS@100 V / 2.5 W RMS@70 V (2000 Ohm) 2.5 W RMS@100 V / 1.25 W RMS@70 V (4000 Ohm) Baja Z: 8 Ohm
SENSITIVITY	87 dB (1 W/1 m, EN 54-24) 75 dB (1 W/4 m, EN 54-24)
MAXIMUN SOUND PRESSURE	99 dB (Max. W/1 m, EN 54-24) 89 dB (Max. W/4 m, EN 54-24)
COVERAGE ANGLE	H/V: 360°@500Hz, 230°@1kHz, 110°@2kHz, 58°@4kHz (-6 dB)
PROTECTION	IP-66 (EN 54-24: Type B)
MATERIAL	ABS plastic Aluminium grille Ceramic connector and thermal fuse Double cable inlet and outlet Stainless steel screws Aluminium mount
SWITCH	W selector in high Z and low Z



+ Info:

<https://fonestar.com/PF-1020T-EN>

CONNECTORS	Ceramic connector for cable 3.2 mm Ø (8 mm ²) max.
TEMPERATURE RANGE	Operation: -25°C - +70°C
COLOUR	White (RAL 9010)
DIMENSIONS	137 mm Ø x 200 mm depth
WEIGHT	1.2 kg




+ Info:

<https://fonestar.com/PF-1020T-EN>

SPL


SENSITIVITY



Escala: -:----	A4	Proyecto:	
PF-1020T-EN		Código:	
Autor:		Fecha: 2025-04-07	
Revisado:--		Fecha Revisión: --/--/----	




FONESTAR
Polígono de Trascueto s/n
39600 Revilla de Camargo
Tel: +34 942 254 555
Fax: +34 942 262 777
Web: www.fonestar.es

SPL vs Angle



Escala: -;-;-	A4	Proyecto:	
PF-1020T-EN		Código:	
Autor:		Fecha: 2025-04-07	
Revisado:--		Fecha Revisión: --/--/----	

FONESTAR
Polígono de Trascueto s/n
39600 Revilla de Camargo
Tel: +34 942 254 555
Fax: +34 942 262 777
Web: www.fonestar.es



FONESTAR

Model
PF-1020T-EN

Description
SOUND PROJECTOR WITH 100 V LINE TRANSFORMER
AND LOW IMPEDANCE. EN 54 CERTIFIED

Units
mm

Scale
1:2