

PUBLIC ADDRESS / SPEAKERS / SOUND PROJECTORS

PF-25TD

BIDIRECTIONAL SOUND PROJECTOR



- ✓ Excellent sound quality
- ✓ Bidirectional sound
- ✓ Excellent finish and elegant design
- ✓ IP-55 protection



+ Info:
<https://fonestar.com/PF-25TD>

ESPECIALLY RECOMMENDED IN:



Factories



Education



Transport Stations



All sectors

DESCRIPTION

Two-way sound projector 2 x 5". 10/5/2.5 W RMS@100 V. IP-55 protection. Adjustable fixing mount.

TECHNICAL CHARACTERISTICS

FEATURES	Bidirectional sound projector with 100 V line transformer.
POWER	15 W maximum, 10 W RMS
LOUDSPEAKERS	2 x 5" double cone, varnished cardboard
RESPONSE	130-15,000 Hz
IMPEDANCE	10 W RMS@100V (1,000 Ohm) 5 W RMS@100V (2,000 Ohm) 2.5 W RMS@100V (4,000 Ohm)
SENSITIVITY	91 dB at 1 W/1 m
DISPERSION	Bidirectional 170°@1kHz, 100°@2kHz, 60°@4kHz (-6dB)
PROTECTION	IP55 in compliance with 60529
MATERIAL	ABS high resistance to sun exposure Hermetic casing. Aluminium grille Aluminium mount Stainless steel screws A2
TEMPERATURE RANGE	-25°C ~ 55°C
COLOUR	White (RAL 9016)
DIMENSIONS	138 mm Ø x 200 mm depth
WEIGHT	1.7 kg
ACCESSORIES	Adjustable fixing mount



+ Info:

<https://fonestar.com/PF-25TD>