

PUBLIC ADDRESS / SPEAKERS / CEILING

SKY-5-DOME

5" + 1" LOW IMPEDANCE CEILING LOUDSPEAKER



IP65



SALT MIST RESISTANCE



3-POINT ANCHORAGE



ANTI-DROP SYSTEM



DOME



POWER SELECTOR



TAP-LOCK TERMINALS



TURN-LOCKABLE GRILLE

- ✓ 5" + 1" coaxial speaker. 15 W RMS@8?
- ✓ Protective dome type back cover
- ✓ Low profile aluminium grille
- ✓ Fast connection terminals and high conductivity. In junction box
- ✓ Anti-fall system for installation assistance



+ Info:

<https://fonestar.com/SKY-5-DOME>

ESPECIALLY RECOMMENDED IN:



Hospitality



Retail



Hotels



All sectors

DESCRIPTION

5" coaxial ceiling speaker with 1" tweeter and rear dome cover. 15 W RMS@8 Ohm. Low profile grille.

TECHNICAL CHARACTERISTICS

FEATURES	Low impedance ceiling loudspeaker. Protective dome type back cover. Low profile frameless grille, constructed from rust resistant aluminium. Detachable, turn-lockable. The logo can be removed and the speaker can be painted. Fast connection terminals and high conductivity. Junction box in the rear cover with inlet and outlet port. Anti-fall system for installation assistance. Hook for safety cable. Stable, worm-gear ceiling brackets. Installation in ceilings with limited space. Protection against dust and water.
POWER	15 W RMS 20 W MAX.
SPEAKER	Coaxial loudspeaker. 5" polypropylene woofer 1" swivelling tweeter
RESPONSE	100-20,000 Hz @ -10 dB 120-20,000 Hz @ -3 dB
IMPEDANCE	8 Ohm
SENSITIVITY	86 dB @ 1 W/1 m
SOUND PRESSURE	98 dB @ max. W/1m Continuous 99 dB @ max. W/1m Peak
COVERAGE ANGLE	H/V (-6 dB): 60°@500Hz, 90°@1kHz, 60°@2kHz, 60°@4kHz
PROTECTIONS	IP-65 in compliance with IEC 60529 EN ISO 9227:2006 Neutral Salt Spray Test
MATERIAL	ABS (UV resistant) Liquid paint aluminium grille



+ Info:

<https://fonestar.com/SKY-5-DOME>


CONNECTORS	Highly conductive quick-connect terminals For 0.4 ~ 4 mm ² cross section cable Junction box in the rear cover with inlet and outlet port
OPERATION TEMPERATURE	-20°C ~ 70°C (48 h)
STORAGE TEMPERATURE	10°C ~ 40°C
MAXIMUM HUMIDITY	95%
COLOUR	White (RAL 9003)
DIMENSIONS	Total loudspeaker: 214 mm Ø x 100 mm height Grille section: 5 mm Recessed height: 95 mm Installation hole: 180 mm Ø Maximum ceiling thickness: 30 mm
WEIGHT	1 kg




+ Info:

<https://fonestar.com/SKY-5-DOME>


SPL vs Frequency






SPL vs Angle



Impedance vs Frequency





Product:
SKY-5-DOME + SKY-5T-DOME Line Drawings

Date: 2025-06-12

FONESTAR
www.fonestar.es