

PUBLIC ADDRESS / SPEAKERS / CEILING

SKY-6-DOME

6" + 1" LOW IMPEDANCE CEILING LOUDSPEAKER



IP65



SALT MIST RESISTANCE



3-POINT ANCHORAGE



ANTI-DROP SYSTEM



DOME



FAST-LOCK TERMINALS



TURN-LOCKABLE GRILLE

- ✓ 6" + 1" coaxial speaker. 20 W RMS@8 Ω
- ✓ Protective dome type back cover
- ✓ Low profile aluminium grille
- ✓ Fast connection terminals and high conductivity. In junction box
- ✓ Anti-fall system for installation assistance



+ Info:

<https://fonestar.com/SKY-6-DOME>

ESPECIALLY RECOMMENDED IN:



Hospitality



Retail



Hotels



All sectors

DESCRIPTION

6" coaxial ceiling speaker with 1" tweeter and rear dome cover. 20 W RMS@8 Ohm. Low profile grille.

TECHNICAL CHARACTERISTICS

FEATURES	Low impedance ceiling loudspeaker. Protective dome type back cover. Low profile frameless grille, constructed from rust resistant aluminium. Detachable, turn-lockable grille. The logo can be removed and painted. Fast connection terminals and high conductivity. Junction box in the rear cover with inlet and outlet port. Anti-fall system for installation assistance. Hook for safety cable. Stable, worm-gear ceiling brackets. Installation in ceilings with limited space. Protection against dust and water.
POWER	20 W RMS 25 W MAX.
SPEAKER	Coaxial speaker. 6" polypropylene woofer 1" adjustable tweeter
RESPONSE	45-20,000 Hz @ -10 dB 60-20,000 Hz @ -3 dB
IMPEDANCE	8 Ohm
SENSITIVITY	90 dB @ 1 W/1 m
SOUND PRESSURE	103 dB @ max. W/1m Continuous 106 dB @ max. W/1m Peak
COVERAGE ANGLE:	H/V (-6 dB): 125°@500Hz, 150°@1kHz, 60°@2kHz, 60°@4kHz
PROTECTIONS	IP-65 in compliance with IEC 60529 EN ISO 9227:2006 Neutral Salt Spray Test
MATERIAL	ABS (UV resistant) Liquid painted aluminium grille



+ Info:

<https://fonestar.com/SKY-6-DOME>


CONNECTORS	Highly conductive quick-connect terminals For cable cross-section 0.4 ~ 4 mm². Junction box in back cover with inlet and outlet holes
OPERATION TEMPERATURE	-20°C ~ 70°C (48 h)
STORAGE TEMPERATURE	10°C ~ 40°C
MAXIMUM HUMIDITY	95%
COLOUR	White (RAL 9003)
DIMENSIONS	Total loudspeaker: 249 mm Ø x 95 mm height Grille section: 5 mm Recessed height: 90 mm Installation hole: 219 mm Ø Maximum ceiling thickness: 30 mm
WEIGHT	1.45 kg
ACCESSORIES	Installation template




+ Info:

<https://fonestar.com/SKY-6-DOME>

SPL vs Frequency



SPL vs Angle



+ Info
<https://fonestar.com/SKY-6-DOME>

• Impedance vs Frequency



+ Info
<https://fonestar.com/SKY-6-DOME>