

PUBLIC ADDRESS / SPEAKERS / SURFACE

SONORA-5-DANTE-BK

DANTE SURFACE SPEAKER



- ✓ Crisp, distortion-free sound
- ✓ Digital audio receiver via DANTE
- ✓ Class D amplifier
- ✓ Excellent finish and elegant design
- ✓ Quick and easy installation



+ Info:

<https://fonestar.com/SONORA-5-DANTE-BK>

ESPECIALLY RECOMMENDED IN:



Hospitality



Education



Hotels



All sectors

DESCRIPTION

5 ¼" DANTE surface speaker. 30 W RMS. Adjustable fixing mount. Steel safety cable.

TECHNICAL CHARACTERISTICS

FEATURES	Dante speaker. Class D amplifier. High sound quality, clear sound without distortion.
AMPLIFIER	60 W maximum, 30 W RMS
LOUDSPEAKERS	1 x 5 ¼" polypropylene woofer 1 x 1" tweeter
RESPONSE	80-20.000 Hz
IMPEDANCE	8 Ohm
SENSITIVITY	88.3 dB @ 1 W/1 m
PRESSURE	102.2 dB @ max. W/1 m
COVERAGE ANGLE	H/V: 200°/200°@500Hz, 135°/135°@1kHz, 100°/120°@2kHz, 60°/80°@4kHz (-6 dB)
MATERIAL	ABS (UV resistance) Aluminium mesh grille, with powder-coated finish A2 stainless steel screws
CONNECTORS	1 LAN port for connection to local area network and PoE+, RJ-45 plug
TEMPERATURE RANGE	-10°C ~ 60°C
COLOUR	Black (RAL 9005)
POWER SUPPLY	PoE+ (IEEE 802.3at) or 24 V DC, 2 A
DIMENSIONS	Loudspeaker: 162 x 263 x 147 mm depth Mount wall plate: 68 x 110 mm Loudspeaker with mount: 216 mm depth
WEIGHT	1.7 kg
INCLUDES	Adjustable mounting bracket ± 60° in all directions. Steel safety cable



+ Info:

<https://fonestar.com/SONORA-5-DANTE-BK>

SENSITIVITY (SPL)

